



USING FIELDS & FEATURES

- SR-650-R is a activator agent for discharge printing on polyster, polyamid, acrylic, acetate, wool, silk and their blends.
- Recommended for discharge printing with pigments on dischargeable dyeing with reactive dyes.

PHYSICAL–CHEMICAL PROPERTIES

Appearance: White Crystal Powder

pH : 3.5- 5.2 (20 °C)

Density : 0,95-1.05 g/cm³ (20 °C)

Viscosity : (20 °C) sp: 6, rpm: 10 Brookfield + : 2.500 – 2.800 [mPa.s]

APPLICATION

Mixture

Recommended formulation for having best discharged effect;

SC-021 or SC-381 Sericharge Discharge White or Clear Base 1 kg (1000 gr)

SR-650-R Sericharge Discharge Activator 4-8 %

SAFETY & STORAGE

For optimum shelf life, all products should be stored at moderate temperatures, between 5°C and 30°C. Storage outside of these temperatures may lead to deterioration in the performance of the product.Prevent from freezing.

It should be consumed within 12 months after the production date.

Contact Serimak or supplier for the latest information concerning the compliance of Serimak inks.

In addition users must be aware of potential sources of contamination such as squeegees, flood coaters, screens

and curing equipment which may all contribute trace amounts of restricted phthalate materials from previous use with other inks or additives.



SERIMAK

**SERITEX SERICHARGE
SR-650-R ACTIVATOR
Technical Data Sheet**

Sayfa 2 / 2

PACKING

Available in 1/5 kg containers.

IMPORTANT

The information given above is related to the product mentioned on this brochure and is designed only as using instructions.

It is essential that all batches of fabric and prints are pre-tested under production conditions to ensure that acceptable results and fastness are achieved.